FEATURES

- 1100MHz toggle frequency
- Extended 100E V_{EE} range of –4.2V to –5.46V
- Differential outputs
- Asynchronous Master Reset
- Dual clocks
- Fully compatible with industry standard 10KH, 100K ECL levels
- Internal 75KΩ input pulldown resistors
- Fully compatible with Motorola MC10E/100E151
- Available in 28-pin PLCC package

DESCRIPTION

The SY10/100E151 offer 6 edge-triggered, high-speed, master-slave D-type flip-flops with differential outputs, designed for use in new, high-performance ECL systems. The two external clock signals (CLK_1, CLK_2) are gated through a logical OR operation before use as clocking control for the flip-flops. Data is clocked into the flip-flops on the rising edge of either CLK_1 or CLK_2 (or both). When both CLK_1 and CLK_2 are at a logic LOW, data enters the master and is transferred to the slave when either CLK_1 or CLK_2 (or both) go HIGH.

The MR (Master Reset) signal operates asynchronously to make all Q outputs go to a logic LOW.

BLOCK DIAGRAM



PIN CONFIGURATION



PIN NAMES

Pin	Function
D_0–D_5	Data Inputs
CLK_1, CLK_2	Clock Inputs
MR	Master Reset
Q_0–Q_5	True Outputs
$\overline{Q}_0$–$\overline{Q}_5$	Inverting Outputs
V_{CCO}	V_{CC} to Output

TRUTH TABLES[1]

Asynchronous Operation

Inputs				Output
D_n	CLK_1	CLK_2	MR	$Q_n(t+1)$
X	X	X	H	L

Synchronous Operation

Inputs				Output
D_n	CLK_1	CLK_2	MR	$Q_n(t+1)$
L	u	L	L	L
H	u	L	L	H
L	L	u	L	L
H	L	u	L	H
X	H	u	L	$Q_n(t)$
X	u	H	L	$Q_n(t)$
X	L	L	L	$Q_n(t)$

NOTE:

1. H = HIGH Voltage Level
   L = LOW Voltage Level
   X = Don't Care
   t = Time before positive CLK transition
   t+1 = Time after positive CLK transition
   u = LOW-to-HIGH transition

DC ELECTRICAL CHARACTERISTICS[1]

V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
I_{IH}	Input HIGH Current	—	—	150	—	—	150	—	—	150	µA	—
I_{EE}	Power Supply Current										mA	—
	10E	—	65	78	—	65	78	—	65	78		
	100E	—	65	78	—	65	78	—	75	90		

NOTE:

1. Specification for packaged product only.

AC ELECTRICAL CHARACTERISTICS[2]

V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
f_{MAX}	Max. Toggle Frequency	1100	1400	—	1100	1400	—	1100	1400	—	MHz	—
t_{PLH} t_{PHL}	Propagation Delay to Output CLK MR	 475 475	 650 650	 800 850	 475 475	 650 650	 800 850	 475 475	 650 650	 800 850	ps	—
t_S	Set-up Time, D	0	–175	—	0	–175	—	0	–175	—	ps	—
t_H	Hold Time, D	350	175	—	350	175	—	350	175	—	ps	—
t_{RR}	Reset Recovery Time	750	550	—	750	550	—	750	550	—	ps	—
t_{PW}	Minimum Pulse Width CLK, MR	400	—	—	400	—	—	400	—	—	ps	—
t_{skew}	Within-Device Skew	—	65	—	—	65	—	—	65	—	ps	1
t_r t_f	Rise/Fall Time 20% to 80%	300	450	700	300	450	700	300	450	700	ps	—

NOTE:

1. Within-device skew is defined as identical transitions on similar paths through a device.
2. Specification for packaged product only.

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY10E151JI	J28-1	Industrial
SY10E151JITR*	J28-1	Industrial
SY100E151JI	J28-1	Industrial
SY100E151JITR*	J28-1	Industrial

*Tape and Reel

28 LEAD PLCC (J28-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL, INC. 1849 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 944-0970 WEB http://www.micrel.com

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel, Inc.

© 2002 Micrel, Incorporated.

WWW.ALLDATASHEET.COM

Copyright ⓒ Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com